

Serie NU2

- T-Verbinder
- Steckanschluss mit Überwurfmutter
- Ø 3 Ø 4 Ø 6 Ø 8
- Steckanschluss mit Überwurfmutter
- Ø 3 Ø 4 Ø 6 Ø 8



Betriebsdruck min./max.	-0,95 ... 15 bar
Umgebungstemperatur min./max.	-25 ... 70 °C
Gewicht pro Stück	Siehe Tabelle unten

Technische Daten

Materialnummer	Typ	Anschluss G	Anschluss D	Liefereinheit	Gewicht pro Stück
1823391794	NU2-S-RTK	Ø 3	Ø 3	10 Stück	0,012 kg
1823391795	NU2-S-RTK	Ø 4	Ø 4	10 Stück	0,024 kg
1823391796	NU2-S-RTR	Ø 4	Ø 6	5 Stück	0,026 kg
1823391797	NU2-S-RTK	Ø 6	Ø 6	5 Stück	0,027 kg
1823391798	NU2-S-RTR	Ø 4	Ø 8	5 Stück	0,032 kg
1823391799	NU2-S-RTR	Ø 6	Ø 8	5 Stück	0,035 kg
1823391800	NU2-S-RTK	Ø 8	Ø 8	5 Stück	0,035 kg

Technische Informationen

Einsatz bis -40 °C bei Verwendung mit Druckluftschlauch Serie TU1-S-PAM Ø4x1, Ø6x1, Ø8x1, Ø10x1, Ø12x1,5

Weitere Informationen zu Montage und Toleranzen der verwendbaren Schläuche finden Sie im Dokument „Technische Informationen“ (erhältlich im MediaCentre).

Technische Informationen


Werkstoff

Gehäuse

Messing, vernickelt

Abmessungen

Abmessungen



Abmessungen

Materialnummer	Anschluss D	Anschluss G	L1	L2	SW 1	SW 2
1823391794	Ø 3	Ø 3	20.8	41.2	8	8
1823391795	Ø 4	Ø 4	20	41.2	10	8
1823391796	Ø 6	Ø 4	20	40	12	9
1823391797	Ø 6	Ø 6	20	41	12	9
1823391798	Ø 8	Ø 4	19	44	14	11
1823391799	Ø 8	Ø 6	21	44	14	11
1823391800	Ø 8	Ø 8	22.5	45.5	14	11

Anschluss D = Innendurchmesser des zu verwendenden Schlauches

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



[Facebook.com/EmersonAutomationSolutions](https://www.facebook.com/EmersonAutomationSolutions)



[LinkedIn.com/company/Emerson-Automation-Solutions](https://www.linkedin.com/company/Emerson-Automation-Solutions)



[Twitter.com/EMR_Automation](https://twitter.com/EMR_Automation)

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™