


Air reservoir CRVZS-5

Part number: 192159

FESTO



Data sheet

Feature	Value
Volume	5 l
Operating pressure	-0.095 MPa ... 1.6 MPa
Operating pressure	-13.78 psi ... 232 psi
Short type code	CRVZS
Mounting position	Condensate drain underneath
Conforms to standard	AD 2000
Symbol	00991474
Operating pressure	-0.95 bar ... 16 bar
Certificate issuing authority	CRNOH15669.5C
Operating medium	Compressed air to ISO 8573-1:2010 [-:-:] Nitrogen
CE mark (see declaration of conformity)	In accordance with EU Pressure Equipment Directive
Corrosion resistance class CRC	3 - High corrosion stress
Suitable for use with food	See supplementary material information
Temperature of medium	-10 °C ... 100 °C
Ambient temperature	-10 °C ... 100 °C
Approval	CRN German Technical Control Board (TÜV)
Max. tightening torque for connecting thread	130 Nm
Max. tightening torque for condensate drain	27 Nm
Product weight	3581 g
Type of mounting	With through-hole
Condensate drain connection	G3/8
Pneumatic connection	G1
Note on materials	Copper/PTFE-free RoHS-compliant
Material air reservoir	High-alloy stainless steel